



Copper Network Patch Leads

Copper Network Patch Leads (CAT5e, 6, 6A)

Features

- Low smoke zero halogen jacket allows for deployment in controlled data centre environments
- Range of jacket and boot colours for network designation & well suited to defence requirements
- Snagless boots with integrated strain relief offer protection to patch leads during handling and patching
- S/FTP Category 6A patch leads suitable for high bandwidth environments susceptible to radio or electromagnetic interference

Application

- Defence networks
- Communications closet or cabinet patching
- Terminal patching
- Temporary communication links

Design

Complies with all TIA 568.C.2 Category 5e, 6 or 6A requirements

Product Information

LSZH Construction

Technical Information

Product Color	Various
Temperature, Operation [°C]	-25 ~ 60 °C
Temperature, Storage [°C]	-25 ~ 60 °C
Temperature, Installation [°C]	-10 ~ 50 °C
Conformance	• ISO/IEC11801:2011(Ed. 2.2) • ANSI/TIA/EIA-568-C.2 • EN 50173-1:2011 • EN 50173-2:2007 including amendment A1:2010 • IEC61935-2:2010(Ed.3.0) (transmission requirements) • RoHS Compliant
Technical Notes	Operating Frequency: - TIA 568 Category 5e (U/UTP): 100MHz - TIA 568 Category 6 (U/UTP & F/UTP): 250MHz - TIA 568 Category 6A (U/UTP & F/UTP): 500MHz
Ordering Information	Patch leads are packed individually in press seal bags